DEVELOPMENT REVIEW BOARD REPORT



MEETING DATE: May 18, 2006 ITEM NO. 4-DR-2006 CASE NUMBER/ **Woodmere Condominiums PROJECT NAME** 4804 & 4816 N. Woodmere Fairway LOCATION Request approval of a site plan and elevations for a new condominium project REQUEST which will be constructed to replace the existing multi-family units. Camberlango Properties, N/A**ENGINEER OWNER** Inc. 480-993-0560 LEA-Architects, LLC Lance Enyart ARCHITECT/ APPLICANT/ 602-943-7511 LEA-Architects, LLC COORDINATOR **DESIGNER** 602-943-7511

BACKGROUND

Zoning.

The site is zoned multi-family residential (R-5). The R-5 zoning category allows multifamily residential uses, ranging up to a maximum density of 23 units per acre.

Context.

The site is located on Woodmere Fairway, south of Chapparal Road. It is located just north of the Downtown boundary, in an area with primarily multi-family residential projects which were constructed in the late 1960's and 1970's. Directly across Woodmere Fairway is the old Hotel Ivy, which is currently proposed for redevelopment under the project name "Reflections on the Canal" (The Board saw the Reflections project at Study Session on April 20, 2006).

Adjacent Uses:

- North: Multi-family housing in the R-5 zone district.
- South: Multi-family housing in the R-5 zone district.
- East: The old Hotel Ivy site, proposed for redevelopment into Multifamily housing in the R-5 zone district.
- West: Multi-family housing in the R-5 zone district.

APPLICANT'S PROPOSAL

Applicant's Request.

The applicant is requesting approval of site plans, floor plans, elevations, landscape plans, and lighting plans for the redevelopment of an existing multifamily project located on Woodmere Fairway, south of Chapparal Road. This project would include 2 separate buildings, with a detached garage structure, totaling 11 residential units.

The applicant is proposing to construct a relatively modern structure, utilizing gray sandblasted masonry, gray metal siding, steel beams and trellises, green insulated glass, and yellow/gold EIFS in small application. Each unit would have a raised porch and balcony. Access would be provided along the eastern edge of the property to attached garages for Building A, and along the alley to a detached garage for Building B (Those units fronting Woodmere Fairway). Open space is provided to the interior of the site, and includes a pool and patio space. The applicant is proposing 36 inch box desert museum shade trees along Woodmere Fairway, and 24 inch box Acacia trees on the interior of the site, as well as a mix of shrubs and groundcover.

Development Information:

Existing Use: Multi-Family Residential
 Proposed Use: Multi-Family Residential
 Parcel Size: 32, 782 Square Feet

• Building Sizes: Building A – 7190 Square Feet

Building B – 7212 Square Feet

Unit Sizes – 1202 – 1438 Square Feet

Building Height Allowed: 36 Feet
Building Height Proposed: 35 Feet
Parking Required: 17 Stalls
Parking Provided: 18 Stalls

Open Space Required: 5,700 Square Feet
Open Space Provided: 9,229 Square Feet

Number of Units: 11 UnitsDensity: 15 du/acre

DISCUSSION

The proposal for a relatively modern structure at this location is somewhat of a departure from the traditional development in the area; but not in a negative sense. The context of the area is such that a myriad of styles and treatments exist in the built environment. Some are good, some the City would probably not wish to be repeated.

In this situation, the applicant is proposing two structures to be constructed of sandblasted masonry and metal siding (primarily), with stucco accents, and steel beams and trellises. The structure is articulated by movement diagonally between the masonry and the metal on the side of the building, and also vertically on the front toward Woodmere Fairway with the metal element. The front façade is articulated in the recesses by the EIFS, balconies, and steel beams/trellises. Overall, the architectural character works for this project is appropriate because it helps create the sense of place that the R-5 district contemplates with higher density housing alternatives. The units front on Woodmere Fairway, rather than turn their back to the roadway. The architecture, while not identical to what is in this neighborhood, will offer an alternative which is still in context with the surrounding multi-family environment and not reinforce a 1970's stucco theme which is somewhat prevalent in the area.

The applicant is proposing landscaping which is appropriate for the area, and is

providing shade trees along Woodmere Fairway, and Acacia trees around the interior of the site. This planting palate achieves two objectives. Firstly, the shade trees accomplish the overall City goal of providing shade along pedestrian paths, and second, these trees will help frame the front of the structure, with its raised front entry points, from Woodmere Fairway.

OTHER BOARDS AND COMMISSIONS

None. The Development Review Board's decision is final in this matter, unless a timely appeal is filed with the City Clerk of the City of Scottsdale.

STAFF

RECOMMENDATION

Staff recommends approval, subject to the attached stipulations.

STAFF CONTACT(S)

Mac Cummins, AICP

Principal Planner Phone: 480-312-7059

E-mail: mcummins@ScottsdaleAZ.gov

APPROVED BY

Mac Cummins, AICP

Report Author

Lusia Galav, AICP

Director, Current Planning Phone: 480-312-2506

E-mail: lgalav@scottsdaleAZ.gov

ATTACHMENTS

- 1. Applicant's Narrative
- 2. Context Aerial
- 2A. Aerial Close-Up
- 3. Zoning Map
- 4. Site Plan
- 5. Landscape Plan
- 6. Elevations
- A. Fire Ordinance Requirements
- B. Stipulations/Zoning Ordinance Requirements

Located near Old Town Scottsdale, the Woodmere Condominiums consist of five three level units with attached garages and seven two level units with detached garages. The architecture utilizes natural materials to provide refuge while also providing a connection to the environment through framed views and common space. Deep roof overhangs, steel shade hoods, and balcony projections wrap the buildings, providing shade and privacy while remaining respectful of the neighborhood context. The living space is elevated above the FEMA flood plain, which allows for, elevated decks, and views into and beyond the serene desert courtyard.

The project implements energy efficient design strategies with green building systems and materials. Native desert vegetation will be used throughout the project, utilizing a xeriscape planting strategy to conserve water. Over one quarter of the total site area is dedicated to open common space, a pool and spa. A two-car garage, self-contained within the 2 and one-half level units, provides ten onsite parking spaces. Seven detached garages and 3 onsite parking stalls adjacent to the alley provide 10 additional spaces for the two level loft style units. Total on-site parking is twenty spaces. The primary vehicular drive runs along the northeast edge of the site and is accessible from Woodmere Fairway and the alley to the northwest. It is anticipated that no onsite water retention will be required due to the small size of the site.


Currently the site contains 8 multifamily units, an existing pool and spa, and covered parking accessible off the alley to the north. The existing units are in poor condition, and will be completely demolished and removed prior to the start of new construction.




ATTACHMENT #2



ATTACHMENT #2A



3 SOUTH STREETSCAPE @ WOODMERE





STE PLAK AND STREETSCAPES 4-DR-2006 HOISIVE

the states to a sufficient of times. If there is no new control or control of the sufficient success of the succ

REV: 3/31/2006 LEA - ARCHITECTS, LLC

1730 EAST NORTHERN PHOENIX, AZ







WATER INTENSIVE PLANT CALCULATION

TOTAL SITE: 28,266 SQ.FT.

ALLOWED: 1,863 SQ.FT. PROVIDED: 0 SQ.FT.

TOTAL LANDSCAPED AREA
TOTAL PLANTABLE AREA: 6,732 SQ. FY.

NUMBER OF MATURE TREES REQUIRED: 9 NUMBER OF MATURE TREES PROVIDED: 12




12.00	Me. IA MILE	ш
By -	Ny 10 10	11.
RHEET TIT CONCEPTI LANDSCAT NEVERN	PE PLAN	$\ $


WOODMERE CONDOMINIUMS






4-DR-2006 REV: 3/31/2006





_	MATERIAL PALETTE				
	MANUFACTURER MATERIAL		COLOR		
(1)	SHERVE	SHE BURIES SHEETS-LIKE MICHIGAN	STREET STEET		
0	BURROUL/ VA JINC	ROOF (LASHING/TASE)	and		
3	SHIRWLY WE THE	METAL STANCING SEAN ROOF	and .		
0	scenate/ w and	METAL SCHOOL	ZiniC		
(3)	Direct Chester	PARTES CIL.	PENTUNE COOKE		
ⅎ	OF THE	STELL BLING ME COLUMNS	CALMACIER		
3	WHENE	ALAN SOCIAL PRINCIPLE FRANK	CLEAR AMERICA CLIFE.		
(1)	MC	MOLLAND GLASS	SOLARUREDI. DELARROA		
®	ZYNERCY	US NOW	POPPLINE COOKE		
0	ONEMEND DIVIR	SCENORIC DEMICIO DICIR	CACUMMENTED		
0	OVERHENE SOOP	SECTIONAL OVERHEAD DOOR	MICH DATE		



4-DR-2006 REV: 3/31/2006


PRELIMINARY, NOT FOR CONSTRUCTION OR RECORDING




WOODMERE CONDOMINIUMS 4804-4832 North Woodmere Felrway










	MATERIAL PA	LETTE	Act -
	MANUFACTIONER	MATERIAL.	DOLOR
0	SUPPRINT	SHO BLOSSO SHOOM-FACE MACHINE	SCHOOL DECK
0	DESIRECT/ YE SHE	SCOT PLASHRE/THSCH	290
3	SURPLY WITH	WERE SEWERG SEW MOOF	ZHC
0	SERVICE/ WI ZNC	NCK SING	ZMC
٩	reatt	mores tit.	
1	us sma	THE BLAS ME COLUMN	CALMARITI
0	EARNESS	ALIE COOK/MICHIE FRANK	CLOW ARROSTS ALIK
(1)	PFG	HOLLAND GLAND	SOLVEDBER GELWINDA
(B)	SWEREY	CES TRUM	-
0	DADHIEVE DOOR	SICTIONS, IMPRICAD DOOR	CHEMIST
0	OMERNICACO DOCUME	SCHOOL DERIVE TOTAL	ARRESTS NUM. Wile SLATED

+11-4 (100 100) +11-4 (100 100) +11-4 (100 100) +11-4 (100 100) +11-4 (100 100) +11-4 (100 100) +11-4 (100 100) +11-4 (100 100)
WEST ELEVATION - UNIT B



4-DR-2006 REV: 3/31/2006

PRELIMINARY, NOT FOR CONSTRUCTION OR RECORDING


ARE 03-33-00 (Max 0.450 Max 0.450 Ma

OODMERE CONDOMINIUMS

LEA - ARCHITECTS, LLC
1730 EAST NORTHERN PHOENIX, AZ
ARCHITECTURE PLANSING MITERIORS GONEYRUGITON MOST







north streetscape at alley





SAFETY RADIO AMPLIFICATION SYSTEM.

DATE: 1/24/2006

Woodmere Condomuniums 4804-4832 N Woodmere Fairway Scottsdale, AZ

FIRE ORDINANCE REQUIREMENTS

(INCORPORATE INTO BUILDING PLANS AS GENERAL NOTE BLOCK - USE ONLY THE DESIGNATED STIPULATIONS)

⊠ 1	. PREMISES INDENTIFICATION TO BE LEGIBLE FROM STREET OR DRIVE & MUST BE ON ALL PLANS.	⊠ 11.	BACKFLOW PREVENTION WILL BE REQUIRED ON VERTICAL RISER FOR CLASS 1 & 2 FIRE SPRINKLER SYSTEMS PER SCOTTSDALE
⊠ 2	PROVIDED & MARKED IN COMPLIANCE WITH CITY		REVISED CODE.
	ORDINANCE & IFC AT THE FOLLOWING LOCATIONS.	⊠ 12.	PROVIDE ALL WEATHER ACCESS ROAD (MIN. 16') TO ALL BUILDINGS & HYDRANTS FROM PUBLIC WAY
	AS SHOWN		DURING CONSTRUCTION.
	<u> </u>	□ 13.	SEE APPROVED CIVILS FOR THE NUMBER OF FIRE
⊠ 3	B. IT IS THE DEVELOPERS RESPONSIBILITY TO DETERMINE ULTIMATE COMPLIANCE WITH THE FAIR HOUSING ADMENDMENTS ACT & AMERICANS WITH DISABILITIES ACT & INCORPORATE SAME INTO THEIR BUILDING PLANS.		HYDRANTS REQUIRED. DEVELOPER SHALL HAVE THE REQUIREDHYDRANTS INSTALLED & OPERABLE PRIOR TO THE FOOTING INSPECTION. HYDRANTS SHALL BE SPACED AT A MAXIMUM OF AT GPM. THE DEVELOPER SHALL MAKE THE C.O.S. APPROVED CIVIL WATER PLANS AVAILABLE TO THE FIRE SPRINKLER CONTRACTOR
	. SUBMIT PLANS & SPECS FOR SUPERVISED	_	
	AUTOMATIC EXTINGUISHING SYSTEM FOR ALL COOKING APPLIANCES, HOOD PLENUMS & EXHAUST DUCTS.	∐ 14.	PORTABLE FIRE EXTINGUISHERS SHALL BE INSTALLED. SEE SHEET(S)
		□ 15.	EXIT & EMERGENCY LIGHTING SHALL COMPLY
⊠ 5	 i. PROVIDE A KNOX ACCESS SYSTEM: 		WITH THE C.O.S. ORDINANCE & THE IFC. SEE SHEETS
	☐ C. KNOX OVERRIDE & PRE-EMPTION STROBE	□ 16.	SUBMIT MSDS SHEETS & AGGREGATE QUANTITY
	SWITCH FOR AUTOMATIC GATES.	_	FOR ALL HAZARDOUS MATERIALS INCLUDING FLAMMABLES, PESTICIDES, HERBICIDES,
\boxtimes 6	. INSTALL AN AS BUILT DRAWING CABINET		CORROSIVES, OXIDIZERS, ETC.
	ADJACENT TO THE FIRE SPRINKLER RISER. IT SHALL BE OF ADEQUATE SIZE TO ACCOMMODATE		A PERMIT IS REQUIRED FOR ANY AMOUNT OF HAZARDOUS MATERIALS STORED, DISPENSED,
	BOTH THE FIRE SPRINKLER & FIRE ALARM		USED OR HANDLED. COMPLETE AN HMMP & SUBMIT
	DRAWINGS. THE CABINET SHALL BE PROVIDED		WITH THE BUILDING PLANS.
	WITH A LOCK & KEYED TO MATCH THE FIRE ALARM CONTROL PANEL & SUPERVISED BY THE FACP IF	⊠ 17.	FIRELINE, SPRINKLER & STANDPIPE SYSTEM SHALL
	APPLICABLE.	<u>_</u>	BE FLUSHED & PRESSURE TESTED PER NFPA STANDARDS & SCOTTSDALE REVISED CODES.
□ 7	7. SUBMIT PLANS FOR A CLASS FIRE ALARM		
	SYSTEM PER SCOTTSDALE REVISED CODES.	⊠ 18.	FDC SIAMESE CONNECTIONS FOR SPRINKLERS AND/OR STANDPIPES WILL BE LOCATED PER
⊠ 8	3. PROVIDE INTERIOR TENANT NOTIFICATION WHEN		ORDINANCE AND/OR AT AN APPROVED LOCATION.
	OFF-SITE MONITORING IS REQUIRED.		MINIMUM SIZE 2-1/2 x 2-1/2 x 4 (NSHT)
_	(SEE FIRE ALARM INTERPRETATIONS FOR CLARIFICATION)		 ☐ 4' TO 8' BACK OF CURB; INDEP. WET LINE. ☐ WALL MOUNTED - 15' CLEAR OF OPENINGS.
□ 8	O. ADD 2-1/2" WET FIRE HOSE VALVES (NSHT) IF FLOOR AREA EXCEEDS 10,000 SQ. FT. PER FLOOR LEVEL		
	AND/OR IF FIRE DEPT. ACCESS IS LIMITED TO LESS	⊠ 19.	ADEQUATE CLEARANCE SHALL BE PROVIDED AROUND FIRE RISER. DIMENSIONS FROM FACE OF
	THAN 360°		PIPE SHALL MEASURE A MINIMUM OF 12" OFF THE
			BACK OF WALL, 18" ON EACH SIDE & 36" CLEAR IN
□ 1	0. BUILDINGS MAY BE SUBJECT TO INSTALLATION		FRONT WITH A FULL HEIGHT DOOR. THE FIRE LINE SHALL EXTEND A MAXIMUM OF 3' INTO THE
	AND TESTING REQUIREMENTS FOR A PUBLIC		BUILDING FROM INSIDE FACE OF WALL TO CENTER

OF PIPE.

<u>4</u> DR <u>2006</u> DATE: <u>1/24/2006</u>

20.			SPRINKLER SYSTEM SHALL BE INSTALLED TO COMPLY WITH MINIMUM NFPA CRITERIA 2002 EDITION & SCOTTSDALE REVISED CODES. SYSTEMS WITH 100 HEADS OR MORE SHALL HAVE OFF-SITE MONITORING. AFTER BUILDING PLAN REVIEW, INSTALLING CONTRACTOR SHALL SUBMIT (3) THREE COMPLETE SETS OF DRAWINGS & HYDRAULIC CALCULATIONS REVIEWED BY A MINIMUM NICET III DESIGN TECHNICIAN.
	\boxtimes	A.	MODIFIED NFPA 13-D SYSTEM WITH RESIDENTIAL QUICK RESPONSE SPRINKLER HEADS (2002 EDITION)
		В.	MODIFIED NFPA 13R SYSTEM (2002 EDITION) WITH RESIDENTIAL QUICK RESPONSE SPRINKLER HEADS IN DWELLING UNITS & ATTIC AREAS FED FROM SEPARATE FIRELINE PER C.O.S. ORDINANCE & INTERPRETATIONS & APPLICATIONS. CALCULATE UP TO FOUR REMOTE HEADS & 900 SQ FT MIN. IN ATTIC.
		C.	NFPA 13 2002 EDITION COMMERCIAL SYSTEM / DESIGN CRITERIA: SEISMIC DESIGN CATEGORY SHALL BE DETERMINED BY STRUCTURAL ENGINEER.
		D.	THE FIRE SPRINKLER SYSTEM DESIGN FOR WAREHOUSE / STORAGE OCCUPANCIES SHALL BE BASED ON THE FULL HEIGHT CAPACITY OF THE BUILDING PER SCOTTSDALE REVISED CODE. DENSITY CRITERIA:
		E.	SPRINKLER DESIGN CRITERIA FOR UNSPECIFIED WAREHOUSE COMMODITIES: .45 OVER 3000 SQ. FT.
		F.	THE PROJECT SPECIFICATIONS SHALL BE SUBMITTED WITH CONTRACT DRAWINGS.

Submit three (3) complete sets of drawings submitted by installing contractor, after building plan review is complete. Please refer questions to Fire Dept. Plan Review, 312-7070, 312-7684, 312-7127, 312-2372.

Stipulations for Case: Woodmere Condominiums Case 4-DR-2006

Unless otherwise stated, the applicant agrees to complete all requirements prior to final plan approval, to the satisfaction of Project Coordinator and the Final Plans staff.

PLANNING

APPLICABLE DOCUMENTS AND PLANS:

DRB Stipulations

- 1. Except as required by the City Code of Ordinances, Zoning Regulations, Subdivision Regulations, and the other stipulations herein, the site design and construction shall substantially conform to the following documents:
 - Architectural elements, including dimensions, materials, form, color, and texture, shall be constructed to be consistent with the building elevations submitted by LEA-Architects, LLC with a revision date of 03/31/06.
 - b. The location and configuration of all site improvements shall be constructed to be consistent with the site plan submitted by LEA-Architects, LLC with a revision date of 03/31/06.
 - c. Landscaping, including quantity, size, and location of materials shall be installed to be consistent with the conceptual landscape plan submitted by LEA-Architects with a revision date of 03/31/06.

ARCHITECTURAL DESIGN:

- 2. The Developer shall release all existing easements on site that will not be used by new development prior to final plans approval. An application for release of existing easements shall be submitted separately from civil and architectural plan submittals.
- 3. The face of the service entrance section(s) shall be flush with the building façade and painted to match the building.
- 4. All exterior mechanical, utility, and communications equipment shall be screened by parapet or wall that matches the architectural color and finish of the building. Wall or parapet height for roof-mounted units shall meet or exceed the height of the tallest unit. Wall height for ground-mounted units shall be a minimum of 1 foot higher than the tallest unit.
- 5. All exterior conduit and raceways shall be painted to match the building.
- 6. No exterior roof ladders shall be allowed where they are visible to the public or from an off-site location.
- 7. Roof drainage systems shall be interior, except that overflow scuppers are permitted. If overflow scuppers are provided, they shall be integrated with the architectural design.
- 8. Wall enclosures for refuse bins or trash compactors shall be constructed of materials that are compatible with the building(s) on the site in terms of color and texture.
- Dooley wall fencing shall not be allowed.
- 10. All walls shall match the architectural color, materials and finish of the building(s).

LANDSCAPE DESIGN:

DRB Stipulations

11. Upon removal of the salvageable native plants the salvage contractor shall submit completed Native Plant Tracking Form as well as a list identifying the tag numbers of the plants surviving salvage operations to the City's Inspection Services Unit within 3 months from the beginning of salvage operations and/or prior to the issuance of the Certificate of Occupancy.

12. Cut and fill slopes shall be rounded to blend with the existing contours of the adjacent natural grades.

EXTERIOR LIGHTING DESIGN:

DRB Stipulations

- 13. All exterior luminaires shall meet all IESNA requirements for full cutoff, and shall be aimed downward and away from property line, except sign, parking lot canopy and landscape lighting.
- 14. The individual luminaire lamp shall not exceed 250 watts.
- 15. The maximum height from finished graded to the bottom of the any exterior luminaire shall not exceed 20 feet.
- 16. All exterior light poles, pole fixtures, and yokes, including bollards, shall be a flat black or dark bronze.
- 17. Incorporate into the project's design, the following:

Parking Lot and Site Lighting:

- a. The maintained average horizontal illuminance level, at grade on the site shall not exceed 2.5 foot-candles.
- b. The maintained maximum horizontal illuminance level, at grade on the site, shall not exceed 10.0 foot-candles. All exterior luminaires shall be included in this calculation.
- c. The initial vertical illuminance at 6.0 foot above grade, along the entire property line (or 1 foot outside of any block wall exceeding 5 foot in height) shall not exceed 1.5 foot-candles. All exterior luminaires shall be included in this calculation.

Building Mounted Lighting:

- d. All luminaires shall be recessed or shielded so the light source is not directly visible from property line.
- e. Wall mounted luminaires shall contain house side shields, and be mounted on a minimum 4-inch long bracket that is mounted perpendicular to the wall.

Landscape Lighting

- f. All flood light fixtures shall have the internal honeycomb louver (IHL) option.
- g. All landscape lighting directed upward shall utilize the extension visor shields to limit the view of the lamp source.
- h. Landscaping lighting shall only be utilized to accent plant material.
- i. All landscape lighting directed upward, shall be aimed away from property line.
- j. The landscape lighting lamp shall be an incandescent or halogen incandescent source, and shall not exceed 50 watts.

VEHICULAR AND BICYCLE PARKING:

DRB Stipulations

18. Bike rack design shall be in conformance with City of Scottsdale M.A.G. Details unless otherwise approved in writing by the City of Scottsdale's Transportation Department.

ADDITIONAL PLANNING ITEMS:

DRB Stipulations

- 19. No exterior vending or display shall be allowed.
- 20. Flagpoles, if provided, shall be one piece, conical, and tapered.
- 21. Patio umbrellas shall be solid colors and shall not have any advertising in the form of signage or logos.

RELEVANT CASES:

Ordinance

A. At the time of review, the applicable zoning, DRB, Use Permit, and etc. case(s) for the subject site were: 135-DR-1978.

÷

ENGINEERING

The following stipulations are provided to aid the developer in submittal requirements, and are not intended to be all inclusive of project requirements. The developer shall submit engineering design reports and plans that demonstrate compliance with city ordinances, the <u>Scottsdale Revised Code</u> and the <u>Design Standards and Policies Manual</u>.

APPLICABLE DOCUMENTS AND PLANS:

22. Water and Sewer Basis of Design Reports prepared by Four Peaks Development dated March 29, 2006 and April 13th 2006 respectively. Drainage Report prepared by Four Peaks Development dated March 29th 2006. The conceptual Site Plan prepared by Four Peaks Development dated March 31, 2006.

DRAINAGE AND FLOOD CONTROL:

DRB Stipulations

- 23. A final drainage report shall be submitted that demonstrates consistency with the conceptual drainage report approved in concept by the Planning and Development Services Department.
 - a. Before the approval of improvement plans by city staff, the developer shall submit two (2) hard copies and one (1) compact disc copy of the complete final drainage report and plan. The drainage report will reference the current FEMA map and include the required Conditional Letter of Map Revision.

Ordinance

- B. Prior to Final Plan approval the City's Stormwater Management Division must approve a Stormwater Storage Waiver for this development. The Stomwater Waiver will be submitted to the One Stop Shop. This approval is based on the following conditions:
 - (1) Off-site runoff must enter and exit the site as it did historically.
- C. With the final improvement plans submittal to the Plan Review and Permit Services Division, the developer shall submit a final drainage report and plan, subject to City staff approval.
- D. Underground Stormwater Storage:
 - (1) Underground stormwater storage is prohibited unless approval is obtained from the City's Floodplain Administrator.
 - (2) Drywells are not permitted.

ROADWAY, INTERSECTION, AND ACCESS DESIGN:

Streets and other related improvements:

STREET NAME	STREET TYPE	R.O.W. DEDICATION	ROADWAY IMPROVEMENT	CURB TYPE	BIKE PATH, SIDEWALK, TRAILS
N/A	ALLEY	2'	N/A	N/A	N/A
Woodmere	Local	N/A	N/A	Match	6' sidewalk
Fairway	Residential			existing	

DRB Stipulations.

24. The internal streets shall be private. The private street tracts shall be dedicated to provide an emergency and service vehicle access easement.

25. The developer shall design and construct the Woodmere Fairway driveway in general conformance with City of Scottsdale Detail CL-1 with a four, foot landing behind the driveway slope.

INTERNAL CIRCULATION:

Provide a six, foot wide sidewalk along the Woodmere Fairway frontage.

Ordinance

E. Parking areas shall be improved with a minimum of 3" inches of asphalt over 6 inches of aggregate base.

EASEMENTS AND DEDICATIONS

EASEMENT / DEDICATION	DESCRIPTION
12' minimum	Drainage easement
24'	Emergency and Service Vehicle Access Easement over driveway

DRB Stipulations

Sight Distance Easements:

- 26. Sight distance easements shall be dedicated over sight distance triangles.
 - a. Sight distance triangles must be shown on final plans to be clear of landscaping, signs, or other visibility obstructions between 2 feet and 7 feet in height.
 - b. Refer to the following figures: 3.1-13 and 3.1-14 of Section 3.1 of the City's Design Standards and Policies Manual, published December 1999.
- 27. Indemnity Agreements:
 - a. When substantial improvements or landscaping are proposed within a utility easement, an indemnity agreement shall be required. The agreement shall acknowledge the right of the City to access the easement as necessary for service or emergencies without responsibility for the replacement or repair of any improvements or landscaping within the easement.

Ordinance

- F. Waterline and Sanitary Sewer Easements:
 - (1) Before the issuance of any building permit for the site, the developer shall dedicate to the City, in conformance with the <u>Scottsdale Revised Code</u> and the <u>Design</u> Standards and Policies Manual, all water easements necessary to serve the site.

REFUSE:

- 28. Refuse enclosures shall be constructed to City of Scottsdale's standards. Details for construction of trash enclosures can be found in the <u>City of Scottsdale Supplements to MAG Standards</u>.
- 29. Enclosures must:
 - a. Provide adequate truck turning/backing movements for a design vehicle of turning radius R (minimum) = 45 feet vehicle length of L = 40 feet.
 - b. Be positioned to facilitate collection without "backtracking."
 - c. Be easily accessible by a simple route.
 - d. Not require backing more than 35 feet.
 - e. Not be located on dead-end parking aisles.

f. Enclosures serviced on one side of a drive must be positioned at a 30-degree angle to the centerline of the drive.

Ordinance

- G. Refuse enclosures are required as follows:
 - (1) Restaurants: One per restaurant
 - (2) Commercial Building Space: One for 0 to 20,000 s.f., Two for 20,001 to 40,000 s.f., Three for 40,001 to 60,000 s.f., etc.
 - (3) Apartments: One for 0 to 20 units, Two for 21 to 40 units, Three for 41 to 60 units, etc.
- H. Underground vault-type containers are not allowed.
- I. Refuse collection methods, i.e., site plan circulation will be approved at final plan review.
- J. Refuse collection can be provided by the City of Scottsdale's Sanitation Division, at 480-312-5600.

WATER AND WASTEWATER STIPULATIONS

The following stipulations are provided to aid the developer in submittal requirements, and are not intended to be all-inclusive of project requirements. Water and sewer lines and services shall be in compliance with City Engineering Water and Sewer Ordinance, the <u>Scottsdale Revised Code</u> and Sections 4 and 5 of the <u>Design</u> Standards and Policies Manual.

DRB Stipulations

- 30. Where walls cross or run parallel with public water mains, public sewer mains, or public fire lines the following shall apply:
 - a. For walls constructed parallel to these pipes, the walls shall be a minimum of six (6) feet from the outside diameter of the pipe.
 - b. For walls constructed across or perpendicular to these pipes, the walls shall be constructed with gates or removable wall panels for maintenance and emergency access.

WATER:

DRB Stipulations

- 31. Basis of Design Report (Water):
 - a. Before the improvement plan submittal to the Plan Review and Permit Services Division, the developer shall obtain approval of the Water Basis of Design Report from the City's Water Resources Department. The report shall conform to the draft <u>Water and Wastewater Report</u> <u>Guidelines</u> available from the City's Water Resources Department.

Ordinance

K. The water system for this project shall meet required health standards and shall have sufficient volume and pressure for domestic use and fire protection.

WASTEWATER:

- 32. Wastewater Basis of Design Report. Before the improvement plan submittal to the Plan Review and Permit Services Division, the developer shall obtain approval of the Wastewater Basis of Design Report from the City's Water Resources Department. The report shall conform to the draft <u>Water and Wastewater Report Guidelines</u> available from the City's Water Resources Department.
- 33. On-site sanitary sewer shall be privately owned and maintained.

34. Existing water and sewer service lines to this site shall be utilized or shall be abandoned by disconnection at the main.

Ordinance

LOCATION & CLEARANCE.

- L. Privately owned sanitary sewer shall not run parallel within the waterline easement.
- M. All sewage discharged from this development shall meet local and federal pretreatment standards for sewage discharge. The facility may require a City Industrial Users Permit and related monitoring and sampling facility. All development within industrial (I-1) zoned districts shall provide a monitoring manhole.

CONSTRUCTION REQUIREMENTS

DRB Stipulations

As-Built Plans.

- City staff may at any time request the developer to submit as-built plans to the Inspection Services
 Division.
 - a. As-built plans shall be certified in writing by a registered professional civil engineer, using as-built data from a registered land surveyor.
 - b. As-built plans for drainage facilities and structures shall include, but are not limited to, streets, lot grading, storm drain pipe, valley gutters, curb and gutter, flood walls, culverts, inlet and outlet structures, dams, berms, lined and unlined open channels, storm water storage basins, underground storm water storage tanks, and bridges as determined by city staff.

Ordinance

N. Section 404 permits. With the improvement plan submittal to the Plan Review and Permit Services Division, the developer's engineer must certify that it complies with, or is exempt from, Section 404 of the Clean Water Act of the United States. [Section 404 regulates the discharge of dredged or fill material into a wetland, lake, (including dry lakes), river, stream (including intermittent streams, ephemeral washes, and arroyos), or other waters of the United States.]

VERIFICATION OF COMPLIANCE

- 36. Condition for issuance of grading and drainage permit: Before the issuance of a Grading & Drainage Permit:
 - Abandonment of the existing drainage easement and rededication at the proposed location via the Condominium Plat. Final Drainage Report approval including the Conditional Letter of Map Revision.